



| REV | DESCRIPTION | DATE |
|-----|-------------|------|
|     |             |      |
|     |             |      |

|    |                   |         |
|----|-------------------|---------|
| L  | LENGTH            | 24.00mm |
| T  | THICKNESS         | 1.00mm  |
| W  | BLADE WIDTH       | 2.80mm  |
| F  | BLADE LENGTH      | 10.00mm |
| E  | INSULATION LENGTH | 14.00mm |
| D  | INSULATION I.D    | 6.70mm  |
| d1 | BARREL I.D        | 3.40mm  |

|                              |
|------------------------------|
| BASE MATERIAL: COPPER        |
| PLATING: ELECTRO-TINNED.     |
| INSULATION MATERIAL: VINYL.  |
| MAX TEMPERATURE RATING: 75°C |
| MAX WORKING VOLTAGE: 600V    |

|                           |        |                 |  |
|---------------------------|--------|-----------------|--|
| BY                        | DATE   | PART NO: YB10   |  |
| TIM W.                    | Jul-14 |                 |  |
|                           |        |                 |  |
| MAX CURRENT RATING 24AMPS |        | SHEET<br>1 OF 1 |  |
| MATERIAL: COPPER          |        |                 |  |
| FINISH: ELECTRO TINNED    |        |                 |  |
|                           |        | UNITS: mm       |  |
|                           |        | SCALE: n/a      |  |