

## Product Data Sheet HFC210 FIR Cable Ties



Partex Fir Tree (Mountable) Nylon 6.6 Cable Ties

This one piece mountable cable tie has a "Fir Tree" shaped push mount moulded into the head. This head can be pushed directly into a mounting hole, making them a quick and easy solution for securing bundles of cables.

Item No.	Size (mm)	Size (in)	Tensile Strength	Min Bundle Diameter (mm)	Max Bundle Diameter (mm)	UV Resistant
HFC210FIR	4.8x210	8.0	18Kg	3.5	49.5	Black Only

### Material:

Nylon Polyamide 6.6 Natural or Black (specify when ordering)

- Flammability of raw material : UL 94 - V2
- Humidity absorption: 2.7% - 2.8% (23°C @ 50%RH)
- Working Temperature: -40°C + 85°C (-40°F - + 185°F)
- Good resistance to bases, oils, greases, oil derivatives chloride solvents. Limited resistance to acids. Not resistant to phenols.
- REACH, ROHS, PAHS Compliance.
- Minimum Mounting Hole Diameter 6.35mm
- To suit a panel thickness from 1.25-6.35mm

Partex Marking Systems (UK) LTD

61-64 Station Road, Coleshill, Birmingham B46 1JT

Tel: 01675 463670 Fax: 01675 463520 Email: sales@partex.co.uk