

## Product Technical Data Sheet - Nylon Releasable Cable Ties

Partex nylon releasable cable ties are ideal for a wide range of applications. They can be released and reused many times. Manufactured from DuPont Zytel 6.6 nylon they provide high resistance to: brake fluids, lubricants, power steering fluids, oil, grease, paints, lacquers, detergents, animal and vegetable fats, gasoline and alkalis up to 40%.



Material: Nylon 66, self extinguishing UL94 V2  
 Temperature Range: -40° to +85°C  
 Storage temperature: +15° to +30°C at 50% humidity.

Non toxic, recyclable. Halogen free.

**Supplied in bags of 100.**

Part Number*	Dimensions (mm)		Max Bundle Diameter (mm)	Minimum Loop Tensile strength (kg)
	Length	Width		
HFCR100	100	3.6	18	8
HFCR200	200	4.8	50	22
HFCR300	300	4.8	80	22
HFCR380	380	4.8	102	22
HFCR200H	200	7.6	50	22
HFCR300H	300	7.6	80	22
HFCR370H	370	7.6	102	22

\* Please specify required colour when ordering by adding B for black or N for natural to the end of the part number.

Partex Marking Systems (UK) LTD

61-64 Station Road, Coleshill, Birmingham B46 1JT

Tel: 01675 463670 Fax: 01675 463520 Email: sales@partex.co.uk