

Product Technical Data Sheet:

**Coloured Cable Ties**



**Description**

Partex offer a wide range of coloured cable ties.  
Available in Red, Blue, Green, Brown and Yellow (specify colour when ordering).

**Specification**

Material: DuPont Zytel 101F Nylon 6.6 Polyamide  
 Flammability: Self-extinguishing to UL 94-V2  
 Work Temperature: - 40°C to +85°C  
 Recommended storage conditions: +15°C to +30°C 50% Humidity.

High tension, highly resistant against; Brake Fluids, Lubricants, Power Steering Fluids, Oil, Grease, Paints, Lacquer Detergents, Animal and Vegetable Fats, Alkali up to 40% and Gasoline.

Partex Part No	Length (mm)	Width (mm)	Maximum Bundle (mm)	Tensile Strength (kg)
HFC100	100	2.5	18	8
HFC140	140	3.6	33	18
HFC200L	200	2.5	50	8
HFC200	200	4.8	50	22
HFC300	300	4.8	76	22

**Silver Cable Ties**

Ideal for securing wheel trims.



Partex Part No	Length (mm)	Width (mm)	Maximum Bundle (mm)	Tensile Strength (kg)
HFC300 SIL	300	4.8	76	22
HFC365 SIL	370	4.8	102	22

**Partex Marking Systems (UK) LTD**

**61-64 Station Road, Coleshill, Birmingham B46 1JT**

**Tel: 01675 463670 Fax: 01675 463520 Email: sales@partex.co.uk**